

Half Circle Pipe Plugs



Web Page



WhatsApp




E-mail

TAPASAN Half Circle Pipe Plugs are used to temporarily blocking the pipelines with bendies in short pipe distances. It is produced by vulcanizing SBR+NR rubber and high strength fabrics. It is resistant to temperatures between -30°C and +70°C.

Product Code : OV



Connection Type
(R 1/4")



Oval Back Design
for near of pipelines



Friction Increasing
Design

Product Code	Size Usage Range		Max. Working Pressure (bar) / (psi)	Deflated Plug Dimensions		Back Pressure (bar) / (psi)	Approx. Weight (kg) / (lbs)
	Min. Diameter	Max. Diameter		Diameter	Total Length		
	(mm) / (inch)	(mm) / (inch)		(mm) / (inch)	(mm) / (inch)		
OV5070	50 / 2"	100 / 4"	2.5 / 36	45 / 1.8"	145 / 5.7"	0.5 / 7.3	0.2 / 0.4
OV70100	70 / 2.8"	150 / 6"	2.5 / 36	66 / 2.6"	160 / 6.2"	0.5 / 7.3	0.3 / 0.7
OV100150	100 / 4"	200 / 8"	2.5 / 36	93 / 6.4"	190 / 7.4"	0.5 / 7.3	0.6 / 1.3
OV150200	150 / 6"	300 / 12"	2.5 / 36	143 / 9.8"	265 / 10.4"	0.5 / 7.3	0.9 / 2.0