


Joint Test Plugs




TAPASAN Joint Test Plugs are used to provide leaking test at the junction points of GRP and concrete pipes. It is produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C. Thanks to its wheeled structure, it enables easy mobility within the line.

*It can be produced with NBR rubber resistant to gas, petroleum and derivatives.


Product Code : CKTB



Connection Type



Wheels Design



Pipe Type

Product Code	Pipe Diameter (mm) / (inch)	Max. Working Pressure (bar) / (psi)	Deflated Plug Dimensions		Approx. Weight (kg) / (lbs)
			Diameter (mm) / (inch)	Lenght (mm) / (inch)	
ET100	100 / 4"	2.5 / 36	70 / 2.8"	200 / 7.8" + Joint Length	6.0 / 13.2
ET200	200 / 8"	2.5 / 36	150 / 6"	250 / 9.8" + Joint Length	7.0 / 15.4
ET300	300 / 12"	2.5 / 36	250 / 10"	250 / 9.8" + Joint Length	10.5 / 23.1
ET400	400 / 16"	2.5 / 36	350 / 14"	300 / 12" + Joint Length	15.5 / 34.1
ET500	500 / 20"	2.5 / 36	435 / 17"	300 / 12" + Joint Length	30.0 / 66.0
ET600	600 / 24"	2.5 / 36	550 / 22"	300 / 12" + Joint Length	44.0 / 96.8
ET700	700 / 28"	2.5 / 36	650 / 26"	300 / 12" + Joint Length	51.5 / 113.3
ET800	800 / 32"	2.5 / 36	750 / 30"	300 / 12" + Joint Length	59.0 / 129.8
ET900	900 / 36"	2.5 / 36	850 / 34"	300 / 12" + Joint Length	69.2 / 152.2
ET1000	1000 / 40"	2.5 / 36	950 / 38"	300 / 12" + Joint Length	79.4 / 174.6
ET1100	1100 / 44"	2.5 / 36	1050 / 42"	300 / 12" + Joint Length	89.1 / 196.0
ET1200	1200 / 48"	2.5 / 36	1150 / 46"	300 / 12" + Joint Length	98.8 / 217.3
ET1300	1300 / 52"	2.5 / 36	1250 / 50"	300 / 12" + Joint Length	105.6 / 232.3
ET1400	1400 / 56"	2.5 / 36	1350 / 54"	300 / 12" + Joint Length	112.5 / 247.5
ET1500	1500 / 60"	2.5 / 36	1450 / 58"	300 / 12" + Joint Length	126.3 / 277.8
ET1600	1600 / 64"	2.5 / 36	1550 / 62"	300 / 12" + Joint Length	140.0 / 308.6
ET1700	1700 / 68"	2.5 / 36	1650 / 66"	300 / 12" + Joint Length	148.6 / 326.9
ET1800	1800 / 72"	2.5 / 36	1750 / 70"	300 / 12" + Joint Length	157.3 / 346.0
ET1900	1900 / 76"	2.5 / 36	1850 / 74"	300 / 12" + Joint Length	164.0 / 360.8
ET2000	2000 / 80"	2.5 / 36	1950 / 78"	300 / 12" + Joint Length	175.0 / 385.0
ET2100	2100 / 84"	2.5 / 36	2050 / 82"	300 / 12" + Joint Length	184.0 / 404.8