

Lateral Packers



Web Page



WhatsApp



E-mail

TAPASAN Lateral Packers are products that allow point repairs on pipelines. These are produced by vulcanizing SBR+NR rubber and high-strength fabrics. It is resistant to temperatures between -30°C and +70°C.

*Can be produced as a Push Rod compatible head.

Product Code : TB



Connection Type



Back Hook Design



Patch Length Stripes



Push Rod Connection



Push Rod Connection

Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions			Approx. Weight
	Min. Diameter	Max. Diameter		Diameter	Lenght	Total Lenght	
	(mm) / (inch)	(mm) / (inch)		(mm) / (inch)	(mm) / (inch)	(mm) / (inch)	
TB7010006	70 / 2.8"	100 / 4"	3.0 / 44	43 / 1.7"	600 / 23.6"	870 / 34.2	0.6 / 1.3
TB7010010	70 / 2.8"	100 / 4"	3.0 / 44	43 / 1.7"	1000 / 39.3"	1170 / 46.1"	0.8 / 1.7
TB7010015	70 / 2.8"	100 / 4"	3.0 / 44	43 / 1.7"	1500 / 59.0"	1670 / 65.7"	1.1 / 2.4
TB7010020	70 / 2.8"	100 / 4"	3.0 / 44	43 / 1.7"	2000 / 78.7"	2170 / 85.4"	1.4 / 3.0
TB7010030	70 / 2.8"	100 / 4"	3.0 / 44	43 / 1.7"	3000 / 118.1"	3170 / 124.8"	2.0 / 4.4
TB7010040	70 / 2.8"	100 / 4"	3.0 / 44	43 / 1.7"	4000 / 157.4"	4170 / 164.2"	2.8 / 6.1
TB7010050	70 / 2.8"	100 / 4"	3.0 / 44	43 / 1.7"	5000 / 196.8"	5170 / 203.5"	3.4 / 7.5
TB8012510	80 / 3"	125 / 5"	3.0 / 44	45 / 1.7"	1000 / 39.3"	1170 / 46.1"	1.4 / 3.0
TB8012515	80 / 3"	125 / 5"	3.0 / 44	45 / 1.7"	1500 / 59.0"	1670 / 65.7"	2.0 / 4.4
TB8012520	80 / 3"	125 / 5"	3.0 / 44	45 / 1.7"	2000 / 78.7"	2170 / 85.4"	2.3 / 5.0
TB8012530	80 / 3"	125 / 5"	3.0 / 44	45 / 1.7"	3000 / 118.1"	3170 / 124.8"	4.2 / 9.2
TB8012540	80 / 3"	125 / 5"	3.0 / 44	45 / 1.7"	4000 / 157.4"	4170 / 164.2"	5.0 / 11.0
TB8012550	80 / 3"	125 / 5"	3.0 / 44	45 / 1.7"	5000 / 196.8"	5170 / 203.5"	5.7 / 12.5
TB10015010	100 / 4"	150 / 6"	2.5 / 36	64 / 2.5"	1000 / 39.3"	1170 / 46.1"	1.6 / 3.5
TB10015015	100 / 4"	150 / 6"	2.5 / 36	64 / 2.5"	1500 / 59.0"	1670 / 65.7"	2.2 / 4.8
TB10015020	100 / 4"	150 / 6"	2.5 / 36	64 / 2.5"	2000 / 78.7"	2170 / 85.4"	2.6 / 5.7
TB10015030	100 / 4"	150 / 6"	2.5 / 36	64 / 2.5"	3000 / 118.1"	3170 / 124.8"	4.7 / 10.3
TB10015040	100 / 4"	150 / 6"	2.5 / 36	64 / 2.5"	4000 / 157.4"	4170 / 164.2"	5.7 / 12.5
TB10015050	100 / 4"	150 / 6"	2.5 / 36	64 / 2.5"	5000 / 196.8"	5170 / 203.5"	6.5 / 14.3
TB15020010	150 / 6"	200 / 8"	2.5 / 36	89 / 3.5"	1000 / 39.3"	1170 / 46.1"	1.9 / 4.1
TB15020015	150 / 6"	200 / 8"	2.5 / 36	89 / 3.5"	1500 / 59.0"	1670 / 65.7"	2.4 / 5.3
TB15020020	150 / 6"	200 / 8"	2.5 / 36	89 / 3.5"	2000 / 78.7"	2170 / 85.4"	2.8 / 6.1
TB15020030	150 / 6"	200 / 8"	2.5 / 36	89 / 3.5"	3000 / 118.1"	3170 / 124.8"	3.8 / 8.3
TB15020040	150 / 6"	200 / 8"	2.5 / 36	89 / 3.5"	4000 / 157.4"	4170 / 164.2"	4.9 / 10.8
TB15020050	150 / 6"	200 / 8"	2.5 / 36	89 / 3.5"	5000 / 196.8"	5170 / 203.5"	5.3 / 11.6
TB15025010	150 / 6"	250 / 10"	2.5 / 36	102 / 4.2"	1000 / 39.3"	1170 / 46.1"	2.2 / 4.8
TB15025015	150 / 6"	250 / 10"	2.5 / 36	102 / 4.2"	1500 / 59.0"	1670 / 65.7"	2.7 / 6.0
TB15025020	150 / 6"	250 / 10"	2.5 / 36	102 / 4.2"	2000 / 78.7"	2170 / 85.4"	3.2 / 7.0
TB15025030	150 / 6"	250 / 10"	2.5 / 36	102 / 4.2"	3000 / 118.1"	3170 / 124.8"	4.2 / 9.2
TB15025040	150 / 6"	250 / 10"	2.5 / 36	102 / 4.2"	4000 / 157.4"	4170 / 164.2"	5.2 / 11.4
TB15025050	150 / 6"	250 / 10"	2.5 / 36	102 / 4.2"	5000 / 196.8"	5170 / 203.5"	6.2 / 13.6